

## **WHAT IS CLAIMED IS:**

1. In apparatus for supplying a car wash installation with chemical additives which are admixed with the wash water, wherein at least one additive is poured into a cartridge in highly concentrated form, an associated holding device of the car wash for receiving the cartridge, wherein the additive of the cartridge can be removed continuously, according to need, the improvement wherein several additives are poured into several cartridges in highly concentrated form and each cartridge and each associated holding device differs from the other cartridges and associated holding devices, by a mistake-proof flange-mounting.

2. Apparatus according to Claim 1, wherein the cartridge has a snap closure, which can be inserted in a corresponding snap closure of the car wash installation and locked with it.

3. Apparatus according Claim 1, wherein each cartridge has several containers to hold different additives, which can be supplied to various inlets of the car wash installation via the associated holding device.

4. Apparatus according to Claim 1 wherein the additives comprise shampoo, prewash aids, drying aids, wax, and cleaners for car wheel rims.

5. Apparatus according to Claim 1 wherein the car wash installations provide a connecting or metering device for the dilution of the additives or of each additive, in accordance with the application.

6. Apparatus according to Claim 1 wherein at least one additive is present as a solid.

7. Apparatus according to Claim 6, wherein the holding device has a rubbing device to rub out the solid.

8. Apparatus according to Claim 1 wherein at least one additive is present in powder or tablet form.

9. Apparatus according to Claim 8, wherein the car wash installation has a dissolving container for the dissolution of the powdery or tablet-shaped additive and the simultaneous or subsequent dilution.

10. Apparatus according to Claim 1 wherein the additive is present in a highly concentrated liquid or pasty form.

11. Apparatus according to Claim 10, wherein the car wash installation has at least one dissolving container for the dissolution of the liquid or pasty additive and the simultaneous or subsequent dilution.